

ELECTRIC LEG-MOUNTED TILTING MIXER KETTLE

E



SPECIFICATIONS:

Shall be a CROWN Model _____, self-generating, electric kettle. Construction shall be welded stainless steel type 304 satin finish. A double wall kettle interior shall form a steam jacket around the lower 2/3 of the kettle. The bottom of the kettle shall be of hemispheric design for maximum heat transfer. The tubular legs shall be constructed of stainless steel pipe fitted with four hole adjustable flanged feet for securing to the floor. A sealed stainless steel tilt mechanism shall permit the kettle to tilt forward a full 90° for complete emptying. The tilt mechanism shall be self locking for positive stop action.

MIXER FEATURES:

The mixer is a variable speed unit powered by a 5 hp electric motor driving a hydraulic pump. Two agitators shall be included, a primary stainless steel scraper/agitator, and a secondary high speed mixer. Both agitators shall be removable for cleaning and no tools will be required for removal.

The console front to have the main power switch, mixer lift switch and variable speed control.

The bridge is constructed of 10 gauge stainless steel and contains two heavy duty hydraulic motors to drive the agitators. The bridge shall be power tilt, and swing 140° out of the way for kettle tilting or cleaning.

Kettle controls shall include a power switch, indicator light, vacuum/pressure gauge, pressure relief valve and low water shut off. Thermostat range to be 140°F to 285°F (60°C to 140°C), a maximum pressure of 50 psi (345 kPa). Electric elements to be removable.

Model	Capacity
ELTM-40	40 Gallon 152 Litre
ELTM-60	60 Gallon 227 Litre
ELTM-80	80 Gallon 303 Litre
ELTM-100	100 Gallon 380 Litre

OPERATION SHALL BE BY:



Electrically, self-generating closed steam system equipped for operation on:

- 208 Volts, 3 Phase, 60 Hz
- 240 Volts, 3 Phase, 60 Hz

OPTIONAL ITEMS AT EXTRA COST:

- Swing faucet on left console
- 3" manual butterfly valve
- 2" manual butterfly valve
- 316 stainless steel liner for high acid content products
- 33 KW elements
- 380 or 415 VAC, 50 Hz, 3 Phase
- 440, 460 or 480 VAC, 60 Hz, 3 Phase
- 575 or 600 VAC, 60 Hz, 3 Phase (not UL)

SERVICE CONNECTIONS

-  – COLD WATER: 3/8" (10 mm) nominal tubing to kettle fill faucet (Optional)
-  – Electrical connection to be as specified on data plate

ELECTRICAL CHARACTERISTICS

Available kW			AMPS PER LINE								
MODEL	STD.	OPT.	KW	PHASE	208V	220V	240V	380V	415V	480V	600V
ELTM-40	24	N/A	24	3	79.6	75.3	69	43.6	39.9	34.6	27.6
ELTM-60	24	33	33	3	104.6	98.9	90.7	57.2	52.4	44.2	36.3
ELTM-80	24	33									
ELTM-100	24	33									

DIMENSIONS

MODEL	CAPACITY	UNITS	A	B	C	D	E	F	G
ELTM-40	40 U.S. gal. 152 litres	inches mm	26 660	62.25 1581	45.5 1156	55 1397	75.625 1921	15.125 384	56 1422
ELTM-60	60 U.S. gal. 227 litres	inches mm	29.5 749	66 1676	49 1245	58.5 1486	80 2032	19.5 495	58 1473
ELTM-80	80 U.S. gal. 303 litres	inches mm	33 838	69.25 1759	49 1245	58.5 1486	80 2032	19.5 495	60 1524
ELTM-100	100 U.S. gal. 379 litres	inches mm	35.5 902	71.5 1816	49 1245	58.5 1486	85 2159	19.5 495	63 1600

