Australia **Moffat Pty Limited**

Victoria / Tasmania 740 Springvale Road Mulgrave VIC 3170

PO Box 4490, Mulgrave VIC 3170

Phone 03 9518 3888 Fax 03 9518 3833 Email vsales@moffat.com.au

New South Wales Phone 02 8833 4111 Email nswsales@moffat.com.au

South Australia Phone 03 9518 3888 Email vsales@moffat.com.au

Queensland Phone 07 3630 8600 Email qldsales@moffat.com.au

Western Australia Phone 08 9202 6820 Email bgarcia@moffat.com.au

New Zealand Moffat Limited

Rolleston 45 Illinois Drive, Izone Business Hub Rolleston 7675 Phone +64 3 983 6600 Fax +64 3 983 6660 Email sales@moffat.co.nz

Auckland Phone +64 9 574 3150 Email sales@moffat.co.nz







www.moffat.com.au www.moffat.co.nz

©Copyright Moffat Pty Limited Moffat 06.15



Electronic dough sheeter:

Rondostar ECO - the basis.



What makes you successful? A strong base.

The Rondostar ECO is the basic electronic RONDO model with the highest performance, ideal for sheeting and booking. It is extremely reliable, ruggedly constructed, easy to operate and quick to clean. You use it in your bakery to produce a great many dough blocks and dough bands of high quality every day.

For over 60 years now, RONDO has been successfully producing dough sheeters. The extensive experience and expertise are also reflected in the Rondostar ECO - for example in the proven, highperformance drive. Dough-how & more performance at a low price.

Rondostar ECO will convince you:

- Attractive price
- High-performance
- Modern and simple operation
- Colour touchscreen
- Sturdy design
- High degree of reliability
- Simple cleaning





Simple operation

Irrespective of who works with the Rondostar ECO - the quality of your dough blocks and dough bands is always the same. A colour touchscreen with large, language-independent symbols makes operation simple.

Technical data		
Rondostar ECO	SFE 6605.E0	SFE 6607.E0
Version	Stainless steel	Stainless steel
Model	Base	Base
Automatic reeler	Without	Without
Automatic flour duster	optional	optional
Width of conveyor belts	640 mm	640 mm
Table length overall	2720 mm	3320 mm
Roller length	660 mm	660 mm
Safety guard opening	90 mm	90 mm
Roller gap	0.2 – 45 mm	0.2 – 45 mm
Roller gap reduction	By motor: • 100 programs • Manual	By motor: • 100 programs • Manual
Speed of discharge conveyor	85 cm/s	85 cm/s
Rated power	2.0 kVA / 1.2 kW	2.0 kVA / 1.2 kW
Supply voltage	3 × 200 - 480 V, 50/60 Hz	3 × 200 - 480 V, 50/60 Hz
Required floor space (in mm) • in working position, catch pans extended • in resting position	1255 × 3100 1255 × 1780	1255 × 3700 1255 × 2050
Weight	235 kg	255 kg
Options	 Flour catch pans Blue belts Blue scrapers 	 Metal scrapers Pneumatic springs guards

Feet for ship equipment

The right to make changes of a technical nature is reserved. The technical safety and type-specific instructions in the operating manual must be complied with. Prohibition, information and warning signs on the machines are to be complied with in accordance with the operating instructions.



Reliable reversing

Clean photoelectric cells are a requirement for the reliable function of electronic dough sheeters. RONDO photoelectric cells are cleaned automatically with every reverse movement.

SFE 6607H.E0
Stainless steel
Base
With
optional
640 mm
3490 mm
660 mm
90 mm
0.2 – 45 mm
By motor: • 100 programs • Manual
85 cm/s
2.0 kVA / 1.2 kW
3 × 200 – 480 V, 50/60 Hz
1255 × 3700
1255 × 2930
295 kg

and inlet rollers for safety



Automatic flour duster

The automatic flour duster (option) dusts your dough band with flour precisely and evenly. This significantly minimises the amount of flour used.



Gentle reeling

Without any appreciable tension, you reel your dough band with the automatic reeler (option).